

concrete maintenance and repair

polymix

Concrete and Foundation Repair

- Crack and spall repair on concrete floors
- Broken steps and ledges
- Uneven surfaces
- Control joints for high traffic areas
- Sealing separation between foundation and walls
- Stucco and facia repairs
- Repairs on facades

Anchoring

- Custom threads and remounting for minor installations of shelving, pumps, equipment, ECT.
- Re-anchoring grab rails and sidewalk railings
- Re-anchoring fences and barriers
- Recreate custom threads where stripped threads exist

Sealing

- Expansion joints
- Seam areas
- Single and multiple penetrations around roofs
- Where non-structural sealants don't work
 - Areas of high expansion and contraction
 - Door jams
 - High shock areas
 - Barriers
- Electrical boxes
- Refrigeration units

Polymix

PUR113 -115



PUR113

working time: 1 min
bonding time: 5 min
full curing time: 4 h

PUR115

working time: 5 min
bonding time: 15 min
full curing time: 8 h

PUR 113 and PUR 115 are available in thixotropic version or Self Leveling (SL) version.

concrete maintenance and repair

Advantages

- Multi-purpose custom line of products
- Fast repairs
- Fast Bonding
- No odor, solvents or VOCs
- Will not crack, remains flexible
- Waterproof when cured
- Easy to apply, no mixing, weighing or measuring
- No mess
- Sand able and paint able in 10 minutes
- Excellent coefficients of expansion and contraction
- Chemical-resistant
- Structural repairs, not a temporary patch
- Prevents corrosion from returning
- Bonds well to rubber without primer
- High tensile strength absorbs shock, movement and temperature variations



Polymix

PUR113 -115



Inchimica Division of Prospero srl
Via Emidio Villa 17, 42124 Reggio Emilia - Italy
Tel. +39 0522 506161 inchimica@imm-group.net
www.inchimica.net