

Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015

Page n. 1/11

# Plastic Repair & Adhesive Rigid 1 Black parte A

# Safety data sheet

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name Chemical name and synonym Plastic Repair & Adhesive Rigid 1 Black parte A Adesivo a base poliuretanica

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Adesivo a base poliuretanica

1.3. Details of the supplier of the safety data sheet

Name Prospero s.r.l.
Full address via Emidio Villa 17

District and Country 42124 Zona Ind.le Mancasale (RE)

Italy

Tel. 0522 506161 Fax 0522 920553

e-mail address of the competent person

responsible for the Safety Data Sheet a.tirelli@immgroup.it

Product distribution by Alberto Tirelli

1.4. Emergency telephone number

For urgent inquiries refer to +39 3487374228

### **SECTION 2. Hazards identification.**

### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2 H319 Causes serious eye irritation.

#### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words: Warning



Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015

Page n. 2/11

# Plastic Repair & Adhesive Rigid 1 Black parte A

Hazard statements:

H319 Causes serious eye irritation.

Precautionary statements:

P264 Wash . . . thoroughly after handling.
P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing

P337+P313 If eye irritation persists: Get medical advice / attention.

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## **SECTION 3. Composition/information on ingredients.**

#### 3.1. Substances.

Information not relevant.

#### 3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008
		(CLD)

1,1',1",1"'-Ethylenedinitrilotetrapropan-2-ol

CAS. 102-60-3 20 - 50 Eye Irrit. 2 H319

EC. 203-041-4 INDEX. -

Reg. no. 01-2119552434-41-0001 Glicerilpoli(ossipropilen)triammina

CAS. 64852-22-8 1 - 3 Eye Dam. 1 H318, Skin Irrit. 2

H315, Aquatic Chronic 3

H412

EC. -INDEX. -

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### **SECTION 4. First aid measures.**

# 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.



Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015

Page n. 3/11

# Plastic Repair & Adhesive Rigid 1 Black parte A

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

### **SECTION 5. Firefighting measures.**

#### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture.

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

### 5.3. Advice for firefighters.

### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6.** Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.



Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015

Page n. 4/11

# Plastic Repair & Adhesive Rigid 1 Black parte A

#### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

### **SECTION 7. Handling and storage.**

#### 7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

Con un impiego appropriato , non sono necessarie particolarimisure. Protezione anticiendio ed antiesplosione: Evitare l'accumolo di cariche elettrostatiche.

#### 7.2. Conditions for safe storage, including any incompatibilities.

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

Conservare i contenitori ermeticamente chiusi in luogo asciutto e fresco. Le basse temperature o il ghiaccio non danneggiano il prodotto. Proteggere da temperatue superiori a 70 °C. Le proprietà del prod otto cambiano irreversibilmente superando la temperatura limite.

#### 7.3. Specific end use(s).

Information not available.

### **SECTION 8. Exposure controls/personal protection.**

#### 8.1. Control parameters.

### 1,1',1",1"'-Ethylenedinitrilotetrapropan-2-ol

Predicted no-effect concentration - PNEC.		
Normal value in fresh water	0,085	mg/l
Normal value in marine water	0,0085	mg/l
Normal value for fresh water sediment	0,193	mg/kg
Normal value for marine water sediment	0,0193	mg/kg
Normal value for water, intermittent release	1,51	mg/l
Normal value of STP microorganisms	70	mg/l
Normal value for the terrestrial compartment	0,0183	mg/kg



Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015

Page n. 5/11

# Plastic Repair & Adhesive Rigid 1 Black parte A

Health - Derived no-effect level - DNEL / DMEL								
	Effects on				Effects on			
Davida of company	consumers.	Att	05	05	workers	A	Ob	Ob
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND	2,5 mg/kg/d		,		•
Inhalation.			VND	8,7 mg/m3			VND	29,4 mg/m3
Skin.			VND	2,5 mg/kg/d			VND	4,2 mg/kg/d

Legend:

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

#### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### **EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### **SECTION 9. Physical and chemical properties.**

#### 9.1. Information on basic physical and chemical properties.

Appearance liquid
Colour black
Odour Not available.
Odour threshold. Not available.
pH. Not available.



Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015 Page n. 6/11

# Plastic Repair & Adhesive Rigid 1 Black parte A

Melting point / freezing point. Not available. Initial boiling point. > 200 ℃. Not available. Boiling range. Flash point. 182 ℃. Not available. **Evaporation Rate** Flammability of solids and gases Not available. Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. 0.1 Pa Vapour pressure. Not available. Vapour density Relative density. 0,980 Kg/l Solubility Not available. Not available. Partition coefficient: n-octanol/water Auto-ignition temperature. Not available. Not available. Decomposition temperature. 3500 mPas Viscosity Explosive properties Not available. Oxidising properties Not available.

#### 9.2. Other information.

VOC (Directive 2010/75/EC): 0
VOC (volatile carbon): 0

## **SECTION 10. Stability and reactivity.**

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials.

Materie da evitare : acidi forti, ossidanti forti, prodotti chimici reattivi, basi forti

#### 10.6. Hazardous decomposition products.



Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015

Page n. 7/11

Plastic Repair & Adhesive Rigid 1 Black parte A

Information not available.

### **SECTION 11. Toxicological information.**

#### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Glicerilpoli(ossipropilen)triammina LD50 (Oral).2690 mg/kg LD50 (Dermal).12500 mg/kg

## **SECTION 12. Ecological information.**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity.

Glicerilpoli(ossipropilen)triam mina LC50 - for Fish.

68 mg/l/96h

#### 12.2. Persistence and degradability.

Information not available.

### 12.3. Bioaccumulative potential.

Information not available

### 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.



Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015 Page n. 8/11

# Plastic Repair & Adhesive Rigid 1 Black parte A

Information not available.

# **SECTION 13. Disposal considerations.**

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.  Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  CONTAMINATED PACKAGING  Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.
SECTION 14. Transport information.
14.1. UN number.
Not applicable.
14.2. UN proper shipping name.
Not applicable.
14.3. Transport hazard class(es).
Not applicable.
14.4. Packing group.
Not applicable.
14.5. Environmental hazards.
Not applicable.
14.6. Special precautions for user.
Not applicable.



Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015

Page n. 9/11

# Plastic Repair & Adhesive Rigid 1 Black parte A

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

### **SECTION 15. Regulatory information.**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point. 3

Contained substance.

Point. 20 dibutilbis(dodecilitio)s

tannano Reg. no.: 01-2119841260-50-0000

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.



Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015

Page n. 10/11

## Plastic Repair & Adhesive Rigid 1 Black parte A

#### **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Eye Dam. 1 Serious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2

**Aquatic Chronic 3** Hazardous to the aquatic environment, chronic toxicity, category 3

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition



Revision nr. 4

Dated 26/10/2015

Printed on 26/10/2015

Page n. 11/11

# Plastic Repair & Adhesive Rigid 1 Black parte A

- ECHA website

Note for users:
The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

09.