	Prospero s.r.l.	Revision nr. 4
	·	
		Dated 04/12/2017
	PUR 115 parte B	Printed on 04/12/2017
		Page n. 1/12
	Safety data sheet	
SECTION 1. Identification	of the substance/mixture and of the company/under	laking
<b>1.1. Product identifier</b> Product name Chemical name and synonym	PUR 115 parte B Adesivo a base poliuretanica	
	substance or mixture and uses advised against vo a base poliuretanica	
1.3. Details of the supplier of the s	afety data sheet	
Name	Prospero s.r.l.	
Full address District and Country	via Emidio Villa 17 42124 Zona Ind.le Mancasale (RE) Italy	
	Tel. 0522 506161	
	Fax 0522 920553	
e-mail address of the competent pers	on	
responsible for the Safety Data Shee Product distribution by	t a.tirelli@immgroup.it Alberto Tirelli	
<b>1.4. Emergency telephone number</b> For urgent inquiries refer to	+39 3487374228	
SECTION 2. Hazards iden	tification.	

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Acute toxicity, category 4	H332	Harmful if inhaled.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Respiratory sensitization, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.

# 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

	Prospero s.r.l.	Revision nr. 4		
		Dated 04/12/2017		
	PUR 115 parte B	Printed on 04/12/2017		
		Page n. 2/12		
	and the second			
Signal words: Dar	nger			
Hazard statements:				
H332     Har       H373     May       H319     Cau       H315     Cau       H335     May       H334     May       H317     May	spected of causing cancer. mful if inhaled. / cause damage to organs through prolonged or repeated exposure. ises serious eye irritation. ises skin irritation. / cause respiratory irritation. / cause allergy or asthma symptoms or breathing difficulties if inhaled. / cause an allergic skin reaction. htains isocyanates. May produce an allergic reaction.			
Precautionary statements:				
P284         [In c           P304+P340         IF II           P308+P313         IF e	ain special instructions before use. case of inadequate ventilation] wear respiratory protection. NHALED: remove person to fresh air and keep comfortable for breathing. exposed or concerned: Get medical advice / attention. re in a well-ventilated place. Keep container tightly closed.			
Contains: 4,4'	-Methylenediphenyl diisocyanate, oligomers			
2.3. Other hazards.				
On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.				
SECTION 3. Compos	ition/information on ingredients.			
3.1. Substances.				

Information not relevant.

### 3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
CAS. 26447-40-5	55 - 100	Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1A H317

EC. 247-714-0 INDEX. 615-005-00-9

Prospero s.r.l.	Revision nr. 4
	Dated 04/12/2017 Printed on 04/12/2017
PUR 115 parte B	Page n. 3/12

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

# **SECTION 4. First aid measures.**

#### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

# **SECTION 5. Firefighting measures.**

#### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak. UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

## 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

## 5.3. Advice for firefighters.

#### GENERAL INFORMATION

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS



Revision nr. 4

Dated 04/12/2017

Printed on 04/12/2017

PUR 115 parte B

Page n. 4/12

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6.** Accidental release measures.

## 6.1. Personal precautions, protective equipment and emergency procedures.

#### Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

## 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

## 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage.**

## 7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

# 7.2. Conditions for safe storage, including any incompatibilities.

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

# **SECTION 8. Exposure controls/personal protection.**

Prospero s.r.l.	Revision nr. 4
	Dated 04/12/2017
PUR 115 parte B	Printed on 04/12/2017
	Page n. 5/12

#### 8.1. Control parameters.

Regulatory References:

TLV-ACGIH

ACGIH 2014

4,4'-Methylenedipheny		omers						
Threshold Limit Value.								
Туре	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
TLV-ACGIH			0,005					
Predicted no-effect concent	ration - PNEC.							
Normal value in fresh water				1		mg/l		
Normal value in marine wate				0,1		mg/l		
Normal value of STP microc				1		mg/l		
Normal value for the terrest				1		mg/kg	)	
Health - Derived no-eff	ect level - DNEL / D	MEL						
	Effects on				Effects on			
	consumers.				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.	VND	20 mg/kg bw/d						
Inhalation.	0,05 mg/m3	0,05 mg/m3	0,025 mg/m3	0,025 mg/m3	0,1 mg/m3	0,1 mg/m3	0,05 mg/m3	0,05 mg/m3
Skin.	17,2 mg/cm2	25 mg/kg bw/d			28,7 mg/cm2	50 mg/kg bw/d	. 0	. 0

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

#### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

## EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

# RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter

	Prospero s.r.l.	Revision nr. 4
		Dated 04/12/2017
	PUR 115 parte B	Printed on 04/12/2017 Page n. 6/12
L		-

whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9.** Physical and chemical properties.

#### 9.1. Information on basic physical and chemical properties.

Appearance Colour Odour Odour threshold. pH. Melting point / freezing point. Initial boiling point. Boiling range. Flash point. Evaporation Rate Flammability of solids and gases Lower inflammability limit. Upper inflammability limit. Upper explosive limit. Upper explosive limit. Vapour pressure. Vapour density Relative density. Solubility Partition coefficient: n-octanol/water Auto-ignition temperature. Decomposition temperature. Viscosity Explosive properties Oxidising properties	liquid straw-coloured Not available. Not available. Not available. Not available. > 300 °C. Not available. 205 °C. Not available. Not available. Not available. Not available. Not available. Not available. Not available. Not available. 1,220 Kg/l insoluble in water Not available. > 600 °C. Not available. 2000 mPas Not available. Not available. Not available.
9.2. Other information.	

VOC (Directive 2010/75/EC) : VOC (volatile carbon) :

# **SECTION 10. Stability and reactivity.**

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

0

0

10.2. Chemical stability.



PUR 115 parte B

Revision nr. 4

Dated 04/12/2017

Printed on 04/12/2017

Page n. 7/12

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

# 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials.

Information not available.

## 10.6. Hazardous decomposition products.

Information not available.

# **SECTION 11. Toxicological information.**

## 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible carcinogenic effects. Anyway, currently available data do not allow us to comprehensively assess this product.

Acute effects: inhalation of this product is harmful. Exposure symptoms may include: stinging and irritated eyes, mouth, nose, throat; cough, respiratory disorders, dizziness, headache, nausea and sickness. In the most serious cases, inhalation of this product may cause larynx and bronchial tube edema and irritation, chemical pneumonia and pulmonary edema.

This product may cause functional disorders or morphological mutations after repeated or prolonged exposure and/or may accumulate inside the human body and is thus graded as dangerous.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Acute effects: inhalation of this product may irritate the lower and upper respiratory tract and cause cough and respiratory disorders; at higher concentrations it can also cause pulmonary edema. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Inhalation of this product causes sensitization, which may then give rise to a series of inflammatory episodes, most of all characterized by obstruction and affecting the respiratory system. Sometimes, sensitization phenomena arise together with evident rhinitis and asthma. Damages to the respiratory system depend on the inhaled quantity, on the product concentration in the working environment and on the exposure time.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

This product contains isocyanates. Producer's specifications are as follows: Ready-to-use products containing isocyanates may irritate mucosas, particularly those of the respiratory system, and may give rise to hypersensitivity reactions. Vapour or aerosol inhalation may lead to sensitization. Please take all the measures used for all solvent-containing products while manipulating isocyanate-containing products. Avoid vapour and aerosol inhalation. People with allergic or asthmatic precedents or subject to respiratory disorders should not handle products containing isocyanates.

Prospero s.r.l.	Revision nr. 4
	Dated 04/12/2017
PUR 115 parte B	Printed on 04/12/2017
	Page n. 8/12

4,4'-Methylenediphenyl diisocyanate, oligomers LD50 (Oral).> 5000 mg/kg LD50 (Dermal).> 9400 mg/kg LC50 (Inhalation).0,49 mg/l/4h

# **SECTION 12. Ecological information.**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity. Information not available.

#### 12.2. Persistence and degradability.

Information not available.

### 12.3. Bioaccumulative potential.

Information not available.

#### 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

# **SECTION 13. Disposal considerations.**

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information.**

14.1. UN number.

	Prospero s.r.l.	Revision nr. 4
		Deted 04/42/2017
		Dated 04/12/2017 Printed on 04/12/2017
	PUR 115 parte B	Page n. 9/12
Not applicable.		
14.2. UN proper shipping name.		
Not applicable.		
14.3. Transport hazard class(es).		
Not applicable.		
14.4. Packing group.		
NI		
Not applicable.		
14.5. Environmental hazards.		
Not applicable.		
14.6. Special precautions for user.		
Not applicable.		
14.7. Transport in bulk according to	Annex II of MARPOL73/78 and the IBC Code.	
Information not relevant.		
SECTION 15. Regulatory	Information.	
15.1. Safety, health and environme	ental regulations/legislation specific for the substance or mixture.	
Seveso category.	None.	
Restrictions relating to the product or c	contained substances pursuant to Annex XVII to EC Regulation 1907/2006.	
Product.	2	
Point.	3	

		Prospero s.r.l.	Revision nr. 4
			Dated 04/12/2017
		PUR 115 parte B	Printed on 04/12/2017
			Page n. 10/12
Contained substance.			
Point.	56	4,4'- Methylenediphenyl diisocyanate, oligomers	
Substances in Candidate List (Art. 59 F	<u>REACH).</u>		
None.			
Substances subject to authorisarion (A	nnex XIV REACH).		
None.			
Substances subject to exportation repo	orting pursuant to (EC) Re	eg. 649/2012:	
None.			
Substances subject to the Rotterdam C	Convention:		
None.			
Substances subject to the Stockholm C	Convention:		
None.			
Healthcare controls.			
Workers exposed to this chemical ager workers' health and safety are modest	nt must not undergo heal and that the 98/24/EC dir	th checks, provided that available risk-assessment da ective is respected.	ata prove that the risks related to the

# 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16.** Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 2	Carcinogenicity, category 2
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
H351	Suspected of causing cancer.



PUR 115 parte B

Revision nr. 4

Dated 04/12/2017

Printed on 04/12/2017

Page n. 11/12

			Page n. 11/12
H332	Harmful if	inhaled	
H373	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure.		
H319			
H315		rious eye irritation.	
		in irritation.	
H335	•	e respiratory irritation.	
H334	•	e allergy or asthma symptoms or breathing difficulties if inhaled.	
H317 EUH204	,	e an allergic skin reaction.	
LEGEND: - ADR: European Agreemer - CAS NUMBER: Chemical - CE50: Effective concentra - CE NUMBER: Identifier in - CLP: EC Regulation 1272/ DNEL: Derived No Effect I - EmS: Emergency Schedul - GHS: Globally Harmonizer - IATA DGR: International Maritim - INDC: International Maritim - IMDC: International Maritim - INDEX NUMBER: Identifie - LC50: Lethal Concentratio - D50: Lethal dose 50% - OEL: Occupational Exposur - PEC: Predicted environme - PEL: Predicted environme - PEL: Predicted no effect - REACH: EC Regulation 19 - RID: Regulation concernin - TLV: Threshold Limit Valuu - TLV CEILING: Concentrat - TWA STEL: Short-term ex - TWA: Time-weighted aver - VOC: Volatile organic Com-	nt concernir Abstract Se tion (require ESIS (Euro /2008 _evel d System of ir Transpor entration 50 me Code fo e Organizat er in Annex ' n 50% ure Level ulative and ental Conce evel concentrat 207/2006 g the interm e ion that shoc posure limit age exposu pounds very Bioac	d to induce a 50% effect) pean archive of existing substances) classification and labeling of chemicals Association Dangerous Goods Regulation % dangerous goods ion // of CLP toxic as REACH Regulation ntration on ational transport of dangerous goods by train uld not be exceeded during any time of occupational exposure. re limit cumulative as for REACH Regulation	
GENERAL BIBLIOGRAPHY 1. Regulation (EU) 1907/20 2. Regulation (EU) 1272/20 3. Regulation (EU) 790/200 4. Regulation (EU) 2015/83 5. Regulation (EU) 286/201 6. Regulation (EU) 618/201 7. Regulation (EU) 618/201 9. Regulation (EU) 944/201 9. Regulation (EU) 944/201 9. Regulation (EU) 944/201 9. Regulation (EU) 605/201 - The Merck Index 10th E - Handling Chemical Safety - INRS - Fiche Toxicologiqu Patty - Industrial Hygiene a - N.I. Sax - Dangerous prop - ECHA website Note for users: The information contained in thoroughness of provided in	7 06 (REACH 08 (CLP) of 9 (I Atp. CL 0 of the Eur 1 (II Atp. CL 2 (III Atp. C 3 (IV Atp. C 3 (IV Atp. C 3 (V Atp. C 4 (VI Atp. C dition e (toxicolog and Toxicol erties of Inc in the prese formation a	) of the European Parliament the European Parliament P) of the European Parliament pean Parliament P) of the European Parliament LP) of the European Parliament LP) of the European Parliament LP) of the European Parliament LP) of the European Parliament	Jsers must verify the suitability and

Prospero s.r.l.	Revision nr. 4
	Dated 04/12/2017
PUR 115 parte B	Printed on 04/12/2017
	Page n. 12/12

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.